## Climate Controlled Kiosk PC EPC-K436/K436P

43" Ultra Slim Climate Controlled Outdoor Touch Kiosk PC - Intel® i3 / i5 / i7 CPU

## **Product Features:**

- 43" Outdoor Weather-proof Kiosk PC
- Rainproof Projected Capacitive Touch (optional)
- -40° to 60°C Wide Temperature LCD
- 2500nits High Brightness
- Vandal Resistant
- Choice of Landscape or Portrait Style



## **Product Specifications:**

|            | Model Name   | EPC-K436 / K436P   |
|------------|--|--|
| Display    | Size/Type  | 43"  |
|            | Resolution (pixels)  | 1920 x 1080 Full HD  |
|            | Response Time  | 6 m/sec  |
|            | Brightness (cd/m <sup>2</sup> )  | 2500nits Standard  |
|            | Display Style  | Landscape or Portrait  |
|            | Viewing Angle  | 176°H / 176°V  |
|            | Aspect Ratio   | 16:9   |
|            | Glass  | 6mm AR coated Tempered Glass   |
|            | Processor  | Intel® Core i3/i5/i7 – 6 <sup>th</sup> gen CPU   |
|            | Chipset  | NVidia Ion2 support 1080p  |
|            | Memory   | 8GB RMA, 16GB Max  |
|            | Storage  | 120GB SSD, 256GB Max   |
|            | LAN  | 1  |
|            | USB  | 4 x USB 3.0 (1 used by touch)  |
|            | HDMI   | 1  |
| System     | Audio  | In/Out   |
|            |  |  |
|            | Multi-Touch  | Rainproof PCAP (optional)  |
|            | Wi-Fi  | 1 x Wi-Fi Built-in w/ External Antenna   |
|            | Heating/Cooling  | Forced Air Fan Cooling + Heater  |
|            | OS Support   | Windows 10 Pro, Android, Linux   |
|            | Vandal Resistant   | Locks with the enclosure   |
|            | Included   | Scratch resistant paint  |
|            |  | 6mm vandal-proof tempered glass  |
| D          |  | NIG AVROSAD CONIAS CONTROLS OF SWITCHAS  |
| Power      | Power Input  | No exposed cables, controls or switches  |
| Power      | Power Input<br>Color   | AC100~240V   |
| Power      | Color  | AC100~240V<br>Black (Standard); White (Optional)   |
| Power      | Color<br>Construction  | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis   |
| Power      | Color<br>Construction<br>IP rating   | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66   |
|            | Color<br>Construction<br>IP rating<br>Mounting   | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting  |
|            | Color<br>Construction<br>IP rating   | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)  |
|            | Color<br>Construction<br>IP rating<br>Mounting<br>Dimension (mm)   | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)<br>690 x 1220 x 120 (Portrait)                                   |
|            | Color<br>Construction<br>IP rating<br>Mounting<br>Dimension (mm)<br>Net weight                                     | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)<br>690 x 1220 x 120 (Portrait)<br>75kg                           |
|            | Color<br>Construction<br>IP rating<br>Mounting<br>Dimension (mm)<br>Net weight<br>Operating Temp.                  | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)<br>690 x 1220 x 120 (Portrait)<br>75kg<br>-30°~50°C              |
|            | Color<br>Construction<br>IP rating<br>Mounting<br>Dimension (mm)<br>Net weight<br>Operating Temp.<br>Storage Temp. | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)<br>690 x 1220 x 120 (Portrait)<br>75kg<br>-30°~50°C<br>-20°~80°C |
| Mechanical | Color<br>Construction<br>IP rating<br>Mounting<br>Dimension (mm)<br>Net weight<br>Operating Temp.                  | AC100~240V<br>Black (Standard); White (Optional)<br>Aluminum Chassis<br>Front IP66<br>Wall mounting<br>1100 x 775 x 120 (Landscape)<br>690 x 1220 x 120 (Portrait)<br>75kg<br>-30°~50°C              |





