



## TK202III

### Ticket printer

TK202III is a very fast ticket printer, featuring a printing speed > 200mm/s. Different ticket widths, from 20 to 82.5 mm, easily adjustable by the user. Ticket weight (in grams): from 80 to 255 g/m<sup>2</sup>. 1D and 2D barcode printing.




## CHARACTERISTICS

- Ticket printer for heavy workloads
- Printing speed up to 200 mm/s
- Ticket width: from 20 to 82.5 mm
- Ticket weight (in grams): from 70 to 255 g/m<sup>2</sup>
- Improved print head quality for crisp printouts
- Fan-fold / paper roll holder
- Embedded display on 2 lines

## FOCUS ON:

- 1D and 2D barcode printing: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, QR CODE
- RS232 + USB interface
- Sensors: fully adjustable lower and upper optical sensor, to suit any ticket width and to detect black marks/gaps
- The tear-off function is the ideal solution to reduce costs, the cutter does not wear even with labels
- Graphics: dynamic logo (graphic memory max 2MB)
- Characters: True Font character support, any language available

## SOFTWARE:



**PrinterSet SOFTWARE** : to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting, even via LAN.

- Auto-installing drivers for Win 7, 8, 8.1, 10 (32/64 bit compatible), Linux Driver (C.U.P.S.) 32/64 bit compatible
- Custom Power Tool

## TECHNICAL SHEET

<b>Printing Method</b>	Thermal with fixed head
Number of dots	8 dots/mm
Resolution	203 DPI
Printing (mm/sec)	>200 mm/sec
Character set	PC437, PC850, PC860, PC863, PC865, PC858
Printing Format	Height and width from 1x to 8x, reverse, underlined, italic, bold
Printing Direction	Straight, 90°, 180°, 270°
Paper width	From 20mm to 82.5mm (2mm step)
Paper weight	from 70 to 255 g/m <sup>2</sup>
Emulation	CUSTOM/POS - SVELTA
Interfaces	RS232 / USB
Data Buffer	64 KB
Flash Memory	16 MB
Graphic Memory	Dynamic logo management (graphic memory max 2MB)
Drivers	Win 7, 8, 8.1, 10 (32/64 bit compatible) Linux Driver (C.U.P.S.) 32/64 bit compatible
Software Tools	PrinterSet, Custom Power Tool
Power supply	24 Vac ± 10%
Medium consumption	0.8A (12,5% dots turned on)
Head Life	100Km /100M pulses
Dimensions	252.1 (L) x 192.6 (H) x 216 (W) mm
Weight	4 Kg

## MODELS



### 911BD050100313

PRINTER TK202III USB RS232

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 30 November 2020