



I-Series for Android

All-in-One Touchscreen Signage



Integrated Touch



Commercial Grade



2-Year Warranty

Product Overview

The Elo I-Series for Android all-in-one (AiO) combines a commercial-grade touchscreen with the powerful Android Qualcomm® Snapdragon™ processor delivering a responsive AiO computer in a compact size. The AiO system delivers commercial reliability, integrated touch, and flexible mounting options designed to survive the rigors of continuous public use for in-store interaction, point of sale, self-service, wayfinding, corporate and hospitality environments.

Combine the I-Series with Elo's cloud-based management software, EloView® designed to simplify and automate deployment of Elo interactive displays across multiple locations. Deliver a consistent experience automatically across all locations with the EloView software-as-a-service (SaaS) platform that includes OS management (including remote and silent updates), kiosk lock-down, automatic provisioning and device management.

Available in 10", 15" or 22" widescreen sizes with high-performance computing and sleek edge-to-edge glass PCAP touchscreen

Choice of WiFi/Ethernet/ Cellular Connectivity

Optimize deployments with cloud-based configuration, monitoring and scheduling

Modern design with flexible mounting in portrait, landscape and table-top orientation

I-Series for Android Touchscreen Signage

Specifications	10-inch model	15-inch model	22-inch model
Bezel Color	Black		
Diagonal Size	10.1" (256.54mm)	15.6" (396.24mm)	21.5" (545.08mm)
Active Display Area (W x H)	8.54" x 5.34" (216.96mm x 135.60mm)	13.5" x 7.6" (344.16mm x 193.59mm)	18.7" x 10.5" (475.2mm x 267.3mm)
Dimensions* (W x D x H)	10.05" x 7.13" x 0.96" (255.37mm x 181.07mm x 24.45mm)	15.2" x 9.8" x 1.2" (386.7mm x 248.13mm x 30mm)	20.6" x 12.8" x 1.5" (523.8mm x 323.9mm x 37.8mm)
LCD Technology	Active matrix TFT LCD with LED backlight		
Display Technology	1280 x 800 (native) active matrix TFT LCD with LED backlight; Other resolutions supported	Full HD 1920 x 1080 (native) active matrix TFT LCD with LED backlight; Other resolutions supported	Full HD 1920 x 1080 (native) active matrix TFT LCD with LED backlight; Other resolutions supported
Aspect Ratio	16:10	16:9	16:9
Number of Colors	262,144	262,144	16.7 million
Brightness (typical)	LCD Panel 350 nits; with PCAP: 297.5 nits	LCD Panel 300 nits; with PCAP: 255 nits	LCD Panel 250 nits; with PCAP: 215 nits
Response Time (Tr + Tf) (typical)	25 ms	35 ms	14 ms
Viewing Angle (typical)	Horizontal: ±85°; Vertical: ±85°	Horizontal: ±80°; Vertical: ±80°	Horizontal: ±89°; Vertical: ±89°
Contrast Ratio (typical)	800:1	700:1	1000:1
Power Consumption (typical at 110V at 60Hz)	ON: 13W; SLEEP: 3.4W; OFF: 0.2W	ON: 16.5W; SLEEP: 4.0W; OFF: 0.2W	ON: 33.6W; SLEEP: 4.0W; OFF: 0.2W
Input Power	110VAC 60Hz or 230VAC 50Hz via Elo supplied power adapter (included)		
Weight	Unpackaged: 1.43 lbs (0.65 kg) Packaged: 4.4 lbs (2.0 kg)	Unpackaged: 2.9 lbs (1.3 kg) Packaged: 6.8 lbs (3.1 kg)	Unpackaged: 8.2 lbs (3.7 kg) Packaged: 13.8 lbs (6.3 kg)
Shipping Dimensions (WxHxD)	13.18" x 9.72" x 6.53" (335mm x 247mm x 166mm)	18.2" x 12.9" x 6.6" (463mm x 328mm x 170mm)	24.4" x 16.9" x 8.7" (620mm x 430mm x 220mm)
Mounting Options	75 x 75mm	100 x 100mm	100 x 100mm
Warranty	2 years standard. On-site exchange (U.S. only) and extended warranty (U.S. and EMEA) available		
Processor	Qualcomm® Snapdragon™ ARM A15, quad-core 1.7 GHz		
Memory (RAM)	2GB DDR3 RAM, 16GB EMMC Flash		
Connector	Wi-Fi 802.11 b/g/n; Bluetooth 4.0 (BLE) 1x RJ45 Ethernet. Cellular antennas included in the unit; 3G/4G Module (available separately)		
I/O Port	Micro HDMI output; Microphone; Micro SD slot; 3G/4G LTE (Micro SIM card holder); Audio output; Gigabit Ethernet; GPIO support; USB stick support		
AV capability	Front-facing HD webcam; Integrated Earphone Out with Microphone input; Stereo speakers		
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)		
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%		
Regulatory Approvals	Wi-Fi only Models: UL, FCC - Class A, cUL, IC, CB, CE - Class A, CCC, SRRC, EAC, VCCI, MIC Cellular Models: UL, FCC, CB, CE - Class A, PTCRB, GCF		
What's in the Box	I-Series Touchscreen, Power Brick 19V/65W, North America power cable, EU/KR power cable, 2X cable clips, 2X screws for cable clips		

*See dimensional drawings for details

EloView® Features

EloView Portal	<ul style="list-style-type: none"> Log in and manage accounts Remote set up 	<ul style="list-style-type: none"> Application delivery Control of ON/OFF
EloView Device Client	<ul style="list-style-type: none"> Lock screen to kiosk mode Automatically play scheduled app 	<ul style="list-style-type: none"> Lock control buttons (HOME and POWER) Control panel accessible via password that allows network set up and local device settings

Ordering Information

Part Number	Description	Connectivity Type	Touch Technology	Surface Treatment
E021014	ESY10i1-2UWA-0-NA-GY-G	Wi-Fi/Ethernet	PCAP	Clear
E516738	ESY10i1-2UWA-0-AN-GY-M	Wi-Fi/Ethernet with AT&T Cellular	PCAP	Clear
E021574	ESY10i1-2UWA-0-AN-GY-M-VF	Wi-Fi/Ethernet with Vodafone Cellular	PCAP	Clear
E021201	ESY15i1-2UWA-0-AN-GY-G	Wi-Fi/Ethernet	PCAP	Clear
E021767	ESY15i1-2UWA-0-AN-GY-G-M	Wi-Fi/Ethernet with AT&T Cellular	PCAP	Clear
E541788	ESY15i1-2UWA-0-AN-GY-G-M-VF	Wi-Fi/Ethernet with Vodafone Cellular	PCAP	Clear
E021388	ESY22i1-2UWA-0-AN-GY-G	Wi-Fi/Ethernet	PCAP	Clear
E021970	ESY22i1-2UWA-0-AN-GY-G-M	Wi-Fi/Ethernet with AT&T Cellular	PCAP	Clear
E541994	ESY22i1-2UWA-0-AN-GY-G-M-VF	Wi-Fi/Ethernet with Vodafone Cellular	PCAP	Clear

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloView are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2016 Elo Touch Solutions, Inc. All rights reserved. 16101AES00010

