GYIS!011



15 Inch Resistive Touch Value Series Monitor

V15DX-0B-4

VALUE SERIES

GVision's V15DX is a 15" touch screen display designed specifically for use in rugged and harsh point-of-sale (POS) environments. The V15DX has an adjustable base that can be tilted from 0 to 80° and features smart cable management ensuring your unsightly cables and connectors are hidden from your customers. It is the ideal solution for demanding applications that

requires a stable monitor and resilient touch screen.







USB B-Type VGA Analog Touch Input



RS232 Type Touch



Spill/Dust Resistant



010 \$5.99 \$5.99

Total: \$27.26

GVIS!ON

Backlight Unit



SODA POP

COFFEE & TEA

MILKSHAKES

LEMON FIZZ

GREEN TEA

3-Year Warranty

V15DX-OB-459G

15-Inch / 5-Wire Resistive Touch Screen Monitor
















INPUT INTERFACE



GVision's Value resistive touch monitor supports both digital and analog inputs to use as normal desktop monitor with VGA and DVI input or USB-Type B to use touch function as well.

DIMENSION







FEATURES **=**

- 15-Inch Screen Size
- 1024 x 768 Resolution
- Interface: VGA / DVI / RS232 / USB / RJ45
- Supports Customer Display & MSR (Optional)
- Serial RS232 and USB Touch
- Spill & Dust Resistant
- Smart Cable Management
- Resistive Touch Screen
- Built-in USB Hub
- 3-Year Warranty

SPECIFICATIONS

| DISPLAY | V15DX-OB-459G |
|---------------------------|---|
| Screen Size | 15 ln |
| Resolution | 1024 x 768 |
| Backlight | LED |
| Aspect Ratio | 4:3 |
| Viewing Angle | 160° / 160° |
| Response Time | 8ms |
| Brightness | 350cd/m² |
| Contrast Ratio | 800 : 1 |
| Color Depth | 16.7 M |
| Display Area (mm) | 304.1 x 228.1mm |
| INTERFACE | |
| DVI | 1 |
| VGA (15 Pin D-Sub) | 1 |
| USB / RS232 | 1/1 |
| RJ45 | 1 |
| TOUCH TECHNOLOGY | |
| Туре | 5-Wire Resistive |
| Interface | RS-232 or USB-B type or Combo |
| FREQUENCY | |
| Input Frequency | Horizontal: 31.5-60.2 kHz; Vertical: 56.3Hz~75Hz |
| AUDIO | |
| Speakers | Option |
| CABINET | |
| Material | Plastic |
| Color | Black |
| POWER | |
| Consumption | < 20W |
| Electrical Ratings | 12V DC ± 5% (AC 100V ~ 240V, 50/60Hz) |
| TEMPERATURE | |
| Operating | 32° F ~ 104° F (0° C ~ 40° C) |
| DIMENSIONS (WXHXD) | |
| Inch (in) w/o Stand | 14.4 x 11.2 x 2.0 |
| Millimeter (mm) w/o Stand | 365.2 x 286.4 x 51.2 |
| WEIGHT | |
| Net Weight (w/o Stand) | 7.4 lbs (3.5kg) |
| VESA™ | aa (a.ang) |
| Mount Size (mm) | 75 x 75 |
| COMPLIANT | |
| Certification | CE / FCC / LVD |
| Continication | Specifications subject to change without any notice |
| | , |