



LC Essentials 21.5" Customer Kiosk

FEATURES

- + Supports Windows/Chrome/Linux (Optional Android)
- + Modular controller & monitor for ultimate flexibility
- + 21.5" True-Flat PCAP multi-touch screen
- + IP65 Rated monitor for water & dust resistance
- + Optional Printer and PinPad arm
- + Multiple Mounting options
- + Heat Resistance up to 140° F (60° C)
- + 1-Year Warranty

Self-Service Kiosk

Increase efficiency while managing labor costs with self-service kiosks. From self-order to self-checkout, to visitor check-in, ticket purchases, interactive information and more, our self-service hardware options to help you create the perfect interactive experience.

The touchscreen LC Essentials 21.5-inch Customer Kiosk features a high definition screen paired with our powerful display to meet the needs most demanding application.. The modular design enables maximum flexibility with multiple mounting options, and an optional printer and pinpad arm to complete your checkout experience.



LC Essentials 21.5" Customer Kiosk

SYSTEM

Processor: Intel iElkhart Lake J6412
Memory: 4GB or 8GB RAM
Storage: 128GB SSD
Expansion: 1 microSD Card Slot

**For optimal performance, please use microSD UHS-I U1 or Class 10*

DISPLAY

Size and Resolution: 21.5" 1920x1080
Touch Screen: True-Flat PCAP multi-touch

I/O PORTS

USB-Type A: 1 x USB2.0; 3 x USB3.0
USB-Type C: 1 x USB3.0 (Display Port Capable)
Serial Port: 1 x DB9 (Powered RS232) (default: 0V; 5V, 12V)
LAN: 1 x RJ45
HDMI: 1 (HDMI 2.0. 4K @ 60Hz Video)
Display Port: 1 (DP1.4. 8K @ 30Hz Video)
Audio: 1 Mic-in/Line-Out

COMMUNICATION

WLAN+BT: Wi-Fi 6, BT5.2 (Option)

CERTIFICATE

EMC & Safety: FCC Class A, CE Mark, LVD
Monitor: IP65 Rated

ENVIRONMENTAL

Operating temperature: 0°C ~ 35°C (32°F ~ 95°F)
Storing temperature: -20°C ~ 60°C (-4°F ~ 140°F)
Relative humidity: 20% ~ 85% RH non-condensing

DIMENSIONS

L x W x H:
Weight:

MOUNT

Floor VESA 100 x 100
Counter VESA 100 x 100

OS SUPPORTED Windows 10/Linux/Chrome (Optional Android)

