

## PANEL

Screen Size	43"
Native Resolution	3,840 x 2,160 (UHD)
Brightness (Typ., nit)	300
Contrast Ratio	1,200:1
Dynamic CR	1,000,000 : 1 ※ The luminosity ratio of Full Black / Full White color on video input condition.
Color gamut	DCI 80 %
Viewing Angle (H x V)	178 x 178
Color Depth	16.7 Million Colors (8 bit)
Response Time	8 ms (G to G)
Surface Treatment (Haze)	Haze 1%
Operation Hours (Hours / Day)	16 / 7
Portrait / Landscape	Yes / Yes

## CONNECTIVITY

Input	HDMI (3, HDCP 2.2/1.4), USB 2.0 Type A
Output	Audio
External Control	RS232C In / Out (4 Pin Phone Jack), RJ45 (LAN) In

## MECHANICAL SPECIFICATION

Bezel Color	Ceramic Black
Bezel Width	14.0 mm (R/L/T) / 20.2 mm (B)
Weight (Head)	8.0 kg
Monitor Dimensions (W × H × D)	973 × 572 × 85.0 mm
Monitor Dimensions with Stand (W × H × D)	973 × 623 × 216 mm (EU, UK: N/A, stand not provided)
Handle	No
VESA™ Standard Mount Interface	200 x 200 mm

## ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10% to 80%

## POWER

Power Supply	AC 100-240V~, 50/60Hz
Power Type	Built-In Power

## POWER CONSUMPTION

Typ. / Max.	80 W / 115 W
BTU (British Thermal Unit)	273 BTU/Hr (Typ.), 393 BTU/Hr (Max.)

## SOUND

Speaker	Yes
---------	-----

## CERTIFICATION

Safety	CB
EMC	FCC Class "A" / CE / KC
ErP	Yes

## SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
SuperSign Control / Control+	Yes
SuperSign WB	Yes
SuperSign Media Editor	Yes
Signage365Care	Yes (The availability can differ by region.)

## ACCESSORY

Basic	Remote Controller, Power Cord, Regulation Book, Phone to D-Sub9 Gender, Stand (EU, UK: not provided), Cable Holder
-------	--

## GENERAL

Region	Global
--------	--------