

DS-320P-A1 32" PCAP Touch Monitor







Description

The digital signage, DS-320P-Al, is a 32" Full HD (1920 x 1080) projected capacitive, 10 touch solution. This digital signage solution encourages effective and efficient user collaboration and engagement. The ultra slim build coupled with advancements in touch technology, ensures that every user interaction is effortless and effective. Whether it is collaborative applications, way-finding capabilities, or custom branded kiosks, the DS-320P-Al solution retains everything desired in a large format touchscreen.

Featured Specifications

- Size: 31.5" TFT LCD
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1200:1
- Aspect Ratio: 16:9
- Brightness: 400 nits (w/o Touch), 360 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x VGA, 1 x DVI-D, 1 x HDMI
- Warranty: 3 year



Specifications

Touch LCD Display	
Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Туре В)
Screen Treatment	_
I/O Ports	
Serial Port	_
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA, 1 x DVI-D, 1 x HDMI
Audio Port	-
Power Input	1 x AC Power Input
Physical Properties	
Power Supply	AC Input 100~240Vac, 50~60Hz
Speaker	-
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	Front Panel IP65 Compliant
Dimensions (W x H x D) mm	781.5 x 476.6 x 66.8
Net Weight (kg)	15.0
Gross Weight (kg)	18.0
Carton (W x H x D) mm	650 x 945 x 185
VESA	400 x 200 mm
Ball Drop	IK07
Safety	
Certifications	CE, UL/CUL, CCC, ROHS
Environment	
Operating Temperature	0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20° C ~ 60° C, 20% ~ 90% RH. Non-Condensing
Optional Peripheral	
N/A	
•	



The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2021 TES America, LLC. All rights reserved. MT21-1030