

## DT-156P-B2

### 15.6" PCAP Touch Monitor



Stand sold separately
Part #SS-156-A1

#### **Description**

The ultra-modern, unique zero bezel and modular design of the DT-156P-B2 makes it a one-stop-shop solution with optional peripherals for added functionality. This 10-point touch, projected capacitive, Full HD 1920 x 1080 solution is great for retail point-of-sale or point-of-service with add-on features like 3 track MSR and a 2MP camera – two mounting locations, side and top. The seamless bezel, advanced PCAP technology and rounded aesthetic bridges the gap between daily consumer devices and commercial devices, a step towards commonality and memorable end-user experience.

#### **Featured Specifications**

- Size: 15.6" TFT LCD
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- · Aspect Ratio: 16:9
- Brightness: 450 nits (No Touch), 405 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x VGA, 1 x DP, 1 x HDMI
- · Warranty: 3 year



# **Specifications**

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-C
I/O Ports	
Serial Port	1 x RJ11 (for Remote Key)
USB Port	1 x USB Type C (Alt Mode for DP video support)
Video Port	1 x VGA, 1 x DP, 1 x HDMI (up to 1920 x 1080 @60Hz)
Audio Port	1 x Audio-Input (3.5 mm Mini-Jack)
Power Input	1 x DC In 12V Jack Power Input
Physical Properties	
Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	2 x 2W
Housing Color	Black
Construction	Glass, Plastic (ABS), SECC Metal
Compliance	-
Dimensions (W x H x D) mm	369.1 x 223.7 x 27.2 mm (monitor only)
Net Weight (kg)	1.805 kg (monitor only)
Gross Weight (kg)	2.80 kg (monitor only)
Carton (W x H x D) mm	455 x 315 x 150 mm (monitor only)
VESA	100 x 100 mm
Ball Drop	-
Safety	
Certifications	CE, FCC, LVD, RoHS
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
Optional Peripheral	
Camera	CAM-000-A1 (Sold Separately)
MSR	MSR-A1 (Sold Separately)
15.6" Slim Stand	SS-156-A1 (Sold Separately)

