

## **DT-215P-A1**

### 21.5" PCAP Touch Monitor







Stand sold separately
Part #SS-215-A1

#### **Description**

The ultra-modern, unique zero bezel and modular design of the DT-215P-A1 makes it a one-stop-shop solution with optional peripherals for added functionality. This 10-point touch, projected capacitive, Full HD 1920 x 1080 solution is great for retail point-of-sale or point-of-service with add-on features like 3 track MSR and a 2MP camera – one mounting location, the top. The seamless bezel, advanced PCAP technology and rounded aesthetic bridges the gap between daily consumer devices and commercial devices, a step towards commonality and memorable end-user experience.

#### **Featured Specifications**

• Size: 21.5" TFT LCD

• Maximum Resolution: 1920 x 1080

· Contrast Ratio: 1000:1

· Aspect Ratio: 16:9

Brightness: 250 nits (No Touch),
 225 nits (P-CAP)

View Angle: H: 178°, V: 178°

Video Port: 1 x VGA, 1 x DP, 1 x HDMI

· Warranty: 3 year

# **Specifications**

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-C
I/O Ports	
Serial Port	1 x RJ11 (for Remote Key)
USB Port	1 x USB Type C (Alt Mode for DP video support)
Video Port	1 x VGA, 1 x DP, 1 x HDMI (up to 1920 x 1080 @60Hz)
Audio Port	1 x Audio-Input (3.5 mm Mini-Jack)
Power Input	1 x DC In 12V Jack Power Input
Physical Properties	
Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	2 x 2W
Housing Color	Black
Construction	Glass, Plastic (ABS), SECC Metal
Compliance	-
Dimensions (W x H x D) mm	510.96 x 308.01 x 37.9 mm (monitor only)
Net Weight (kg)	4.05 kg (monitor only)
Gross Weight (kg)	8.8 kg (monitor only)
Carton (W x H x D) mm	615 x 405 x 160 mm (monitor only)
VESA	100 x 100 mm
Ball Drop	-
Safety	
Certifications	CE, FCC, LVD, RoHS
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
Optional Peripheral	
MSR	MSR-215-A1 (Sold Separately)
Camera	CAM-000-A1 (Sold Separately)
21.5" Slim Stand	SS-215-A1 (Sold Separately)

