

## IC-156P-AA2 15.6" PCAP Touch Computer





## Description

The IC-156P-AA2 equipped with Rockchip's latest architecture, the RK3399 combining low power consumption and high-performance computing into one integrated PC. The CPU's performance combined with the ultra-slim aesthetic of this AiO works well in any environment. Loaded with the latest Android OS, 9.0 and Google Mobile Services, for easy plug-n-play functionality creates the opportunity for your team to easily incorporate this model into a new or existing application. From POS to an exposed kiosk, self-service to point of information, this product offers peripherals to support - MSR and Camera Module Kit, a wide range of applications, making it a perfect form - fit function solution for a variety of applications.

- Wi-Fi / Bluetooth
- Slim-Bezel Design
- 4GB Memory & 32GB Storage
- MSR (optional)
- Camera Module Kit (optional)
- Speakers (2 x 2W)
- Slim Stand (Optional)
- USB Type-C | HDMI | Micro-SD Slot | LAN Port
- Available as a Monitor only (VGA, DP, HDMI) | DT-156-A1

## **Featured Specifications**

- Size: 15.6" TFT LCD
- Processor: Rockchip RK-3399, Dual-core Cortex-A72 up to 1.8GHz, Quad-core Cortex-A53 up to 1.4GHz
- Maximum Resolution: 1920 x 1080
- Brightness: 450 nits (No Touch), 405 nits (P-CAP)
- View Angle: H:178°, V:178°
- Video Port: 1 x HDMI (1080p 60Hz support), 1 x USB 3.0 Type A, 1 x USB 3.0 Type C (OTG support), 1 x Micro SD Slot (SDHC 2.0 support)
- Warranty: 3 year

## **Specifications**

Touch LCD Display	
Size / Resolution	15.6" TFT LCD / 1920 x 1080
Touch Screen	Projected Capacitive Touch, 10 Points
Brightness (Touch Type)	450 nits (No Touch), 405 nits (P-CAP)
Contrast Ratio	1000:1
View Angle	H:178°, V:178°
Display Surface	7H Hardness durable glass
Camera	-
I/O Ports	
- Serial Port	_
USB Port	1 x USB 3.0 Type A, 1 x USB 3.0 Type C
LAN Port	1 x RJ45 Giga LAN
Video Port	1 x HDMI (1080p 60Hz support)
Power Input	1 x DC in 12V/4.16A 2 pin
SD Slot	1 x Micro SD Slot (SDHC 2.0 support)
	· ·
Operating System Suppo	
OS	Android 9.0 with GMS
<b>Physical Properties</b>	
Speaker	2 x 2W
Material	Plastic, Glass, SECC Metal
Light Bar	-
Housing Color	Dark Gray
Dimensions (W x H x D) mm	369.1 mm x 223.7 mm x 27.2 mm
Net Weight (kg)	1.805 kg
Gross Weight (kg) 2.8 kg	
Carton (W x H x D) mm	455 mm x 315 mm x 150 mm
VESA	100 mm x 100 mm
Safety	
Certifications	CE, FCC, LVD, UL, RoHS
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
Optional Peripheral	
Optional Peripheral MSR	MSR-156-A1 (Sold Separately)
	MSR-156-A1 (Sold Separately) CAM-000-A1 (Sold Separately)



The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2021 TES America, LLC. All rights reserved. MT21-1012