



## M1-156IC-W3-A2

### 15.6" Windows All-in-One Touch Computer











Stand sold separately.

#### **Description**

The Mach M1-156IC-W3-A2 15.6" Windows All-in-One touch computer is a highperformance, versatile, touch computer that combines commercial-grade robustness with a consumer-grade design. This built for purpose computing platform features the unprecedented performance of the 12th generation Intel® Core™ i3 processor. The Mach AIO is equipped with a bright 15.6", full HD, 8-bit, LED panel. It features a projected capacitive, 10-point touch sensor and advanced optical bonding with an etched anti-glare surface. This technology increases clarity and viewing angle, while simultaneously reducing distracting reflections and fingerprints. Smart peripherals include: 2D bar code scanner, multi-color LED status bar, 8MP camera, 3-track MSR, and a port expansion hub. The result is the modern, stylish look you want, the superior performance you need and the versatility for any application.

#### **Featured Specifications**

- Size: 15.6" TFT LCD
- Processor: i3-1215UE 3.3GHz 6 core Gen 12
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- · Aspect Ratio: 16:9
- Brightness: 450 nits (No Touch), 400 nits (PCAP)
- View Angle: H: 178°, V: 178°
- Video Port:

   1 x HDMI
   (up to 1920 x 1080 @60Hz),
   1 x USB-C
   (Alt mode + PD out 12V@3A+USB 2.0)
- · Warranty: 3 year

# **Specifications**

| System Configuration Processor | i3-1215UF 3.3GHz 6 core Gen 12   |
|--------------------------------|--|
| GPU                            |  |
|                                | Intel® UHD Graphics  1 X DDR4 DIMM. slot, 16GB                                     |
| System Memory Storage Device   |  |
| Storage Device TPM             | 1 X M.2 PCI Express 2280, 256GB  |
| Wi-Fi & Bluetooth              | 2.0 for Windows 11 support 802.11 a/b/g/n/ac/ax, Bluetooth 5.2 (Support BLE)       |
| WI-LI & BINGLOOM!              | 802.11 a/b/g/11/ac/ax, Bluetootti 5.2 (Support BLE)                                |
| Touch LCD Display              |  |
| Touch Screen                   | Projected Capacitive, 10 points  |
| Brightness                     | 450 nits (No Touch), 400 nits (PCAP)   |
| Surface Treatment              | Etched Anti-Glare  |
| Contrast Ratio                 | 1000:1   |
| Aspect Ratio                   | 16:9   |
| View Angle                     | H: 178°, V: 178°   |
| Hardness                       | 7H Hardness durable glass  |
| ulo pouto                      |  |
| I/O Ports                      |  |
| USB Port                       | 2 x USB-C (PD in/out) 4 x USB-C (peripheral connection) 4 x USB 3.0 Gen 1 Type A   |
| LAN Port                       | 1 X RJ45 Gigabit Lan   |
| Video Port                     | 1 x HDMI (up to 1920 x 1080 @60Hz)<br>1 x USB-C (Alt mode + PD out 12V@3A+USB 2.0) |
| Audio Port                     | 1 x Audio-Output (3.5 mm Mini-Jack)  |
| Power Input                    | 180W 24V DC in   |
| ·                              |  |
| Operating System               |  |
| OS                             | Windows 10   |
| Physical Properties            |  |
| Speaker                        | 2 x 2W Stereo  |
| Housing Color                  | Black  |
| Construction                   | Plastic, Glass, SECC Metal   |
| Compliance                     | Front Panel IP65 Compliant   |
| Dimensions (W x H x D) mm      | 378.03 x 227.34 x 32 (monitor with stand)  |
| Net Weight (kg)                | 5.46 kg  |
| Gross Weight (kg)              | 7.75 kg  |
| Carton (W x H x D) mm          | 343 x 499 x 171 mm   |
| VESA                           | 100 x 100 mm   |
| Ball Drop / IK                 | IK07   |
|                                |  |

## **Specifications** (cont.)

| Safety                |  |
|-----------------------|--|
| Certifications        | CE, FCC, UL/cUL, NOM, RoHS, UKCA           |
| Environment           |  |
| Operating Temperature | 0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing   |
| Storage Temperature   | -20°C ~ 60°C, 20% ~ 90% RH. Non-Condensing |
| Optional Peripheral   |  |
| Expansion Hub         | MA-HUB-A1                                  |
| MSR                   | MA-MSR-A1                                  |
| Camera                | MA-CAM-A1                                  |
| Light Bar             | MA-LBAR-A1                                 |
| Bar Code Scanner      | MA-SCAN-A1                                 |

