



M1-156|C-W5-A2

15.6" Windows All-in-One Touch Computer











Stand sold separately.

Description

The Mach M1-156IC-W5-A2 15.6" Windows All-in-One touch computer is a highperformance, versatile, touch computer that combines commercial-grade robustness with a consumer-grade design. This built for purpose computing platform features the unprecedented performance of the 12th generation Intel® Core™ i5 processor. The Mach AIO is equipped with a bright 15.6", full HD, 8-bit, LED panel. It features a projected capacitive, 10-point touch sensor and advanced optical bonding with an etched anti-glare surface. This technology increases clarity and viewing angle, while simultaneously reducing distracting reflections and fingerprints. Smart peripherals include: 2D bar code scanner, multi-color LED status bar, 8MP camera, 3-track MSR, and a port expansion hub. The result is the modern, stylish look you want, the superior performance you need and the versatility for any application.

Featured Specifications

- Size: 15.6" TFT LCD
- Processor: i5-1245UE 3.3GHz 10 core Gen 12
- Maximum Resolution: 1920 x 1080
- · Contrast Ratio: 1000:1
- · Aspect Ratio: 16:9
- Brightness: 450 nits (No Touch), 400 nits (PCAP)
- View Angle: H: 178°, V: 178°
- Video Port:

 1 x HDMI
 (up to 1920 x 1080 @60Hz),
 1 x USB-C
 (Alt mode + PD out 12V@3A+USB 2.0)
- · Warranty: 3 year

Specifications

System Configuration	
Processor	i5-1245UE 3.3GHz 10 core Gen 12
GPU	Intel®, Iris® Xe Graphics for i5 CPU
System Memory	1 X DDR4 DIMM. slot, 16GB
Storage Device	1 X M.2 PCI Express 2280, 256GB
TPM	2.0 for Windows 11 support
Wi-Fi & Bluetooth	802.11 a/b/g/n/ac/ax, Bluetooth 5.2 (Support BLE)
Touch LCD Display	
Touch Screen	Projected Capacitive, 10 points
Brightness	450 nits (No Touch), 400 nits (PCAP)
Surface Treatment	Etched Anti-Glare
Contrast Ratio	1000:1
Aspect Ratio	16:9
View Angle	H: 178°, V: 178°
Hardness	7H Hardness durable glass
I/O Ports	
USB Port	2 x USB-C (PD in/out) 4 x USB-C (peripheral connection) 4 x USB 3.0 Gen 1 Type A
LAN Port	1 X RJ45 Gigabit Lan
Video Port	1 x HDMI (up to 1920 x 1080 @60Hz) 1 x USB-C (Alt mode + PD out 12V@3A+USB 2.0)
Audio Port	1 x Audio-Output (3.5 mm Mini-Jack)
Power Input	180W 24V DC in
Operating System	
OS	Windows 10
Physical Properties	
Speaker	2 x 2W Stereo
Housing Color	Black
Construction	Plastic, Glass, SECC Metal
Compliance	Front Panel IP65 Compliant
Dimensions (W x H x D) mm	378.03 x 227.34 x 32 (monitor with stand)
Net Weight (kg)	5.46 kg
Gross Weight (kg)	7.75 kg
Carton (W x H x D) mm	343 x 499 x 171 mm
VESA	100 x 100 mm
Ball Drop / IK	IK07

Specifications (cont.)

Safety	
Certifications	CE, FCC, UL/cUL, NOM, ROHS, UKCA
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 20% ~ 90% RH. Non-Condensing
Optional Peripheral	
Expansion Hub	MA-HUB-A1
MSR	MA-MSR-A1
Camera	MA-CAM-Al
Light Bar	MA-LBAR-Al
Bar Code Scanner	MA-SCAN-A1

