



M1-215IC-W3-A2

21.5" Windows All-in-One Touch Computer



Description

The Mach M1-215IC-W3-A2 21.5" Windows All-in-One touch computer is a highperformance, versatile, touch computer that combines commercial-grade robustness with a consumer-grade design. This built for purpose computing platform features the unprecedented performance of the 12th generation Intel[®] Core[™] i3 processor. The Mach AIO is equipped with a bright 21.5", full HD, 8-bit, LED panel. It features a projected capacitive, 10-point touch sensor and advanced optical bonding with an etched anti-glare surface. This technology increases clarity and viewing angle, while simultaneously reducing distracting reflections and fingerprints. Smart peripherals include: 2D bar code scanner, multi-color LED status bar, 8MP camera, 3-track MSR, and a port expansion hub. The result is the modern, stylish look you want, the superior performance you need and the versatility for any application.

Featured Specifications

- Size: 21.5" TFT LCD
- Processor: i3-1215UE 3.3GHz 6 core Gen 12
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- Aspect Ratio: 16:9
- Brightness: 350 nits (No Touch), 315 nits (PCAP)
- View Angle: H: 178°, V: 178°
- Video Port:
 1 x HDMI
 (up to 1920 x 1080 @60Hz),
 1 x USB-C
 (Alt mode + PD out 12V@3A+USB 2.0)
- Warranty: 3 year

Specifications

System Configuration

| oystern conniguration | • |
|-----------------------|--|
| Processor | i3-1215UE 3.3GHz 6 core Gen 12 |
| GPU | Intel® UHD Graphics |
| System Memory | 1 X DDR4 DIMM slot, 16GB |
| Storage Device | 1 X M.2 PCI Express 2280, 256GB |
| ТРМ | 2.0 for Windows 11 support |
| Wi-Fi & Bluetooth | 802.11 a/b/g/n/ac/ax, Bluetooth 5.2 (Support BLE) |
| | |
| Touch LCD Display | |
| Touch Screen | Projected Capacitive, 10 points |
| Brightness | 350 nits (No Touch), 315 nits (PCAP) |
| Surface Treatment | Etched Anti-Glare |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| View Angle | H: 178°, V: 178° |
| Hardness | 7H Hardness durable glass |
| | |
| I/O Ports | |
| USB Port | 2 x USB-C (PD in/out) 4 x USB-C (peripheral connection) 4 x USB 3.0 Gen 1 Type A |
| I AN Port | 1 X P 1/5 Giaghit Lap |

| LAN Port | 1 X RJ45 Gigabit Lan | |
|-------------|--|--|
| Video Port | 1 x HDMI (up to 1920 x 1080 @60Hz) 1 x USB-C (Alt mode + PD out 12V@3A+USB 2.0) | |
| Audio Port | 1 x Audio-Output (3.5 mm Mini-Jack) | |
| Power Input | 180W 24V DC in | |

Operating System

| OS | Windows 10 |
|----------------------------|---|
| Physical Properties | |
| Speaker | 2 x 2W Stereo |
| Housing Color | Black |
| Construction | Plastic, Glass, SECC Metal |
| Compliance | Front Panel IP65 Compliant |
| Dimensions (W x H x D) mm | 515.44 x 366.08 x 111.66 (monitor with stand) |
| Net Weight (kg) | 10.85 kg |
| Gross Weight (kg) | 13.25 kg |
| Carton (W x H x D) mm | 493 x 638 x 242 mm |
| VESA | 100 x 100 mm |
| Ball Drop / IK | IK07 |

Specifications (cont.)

| Safety | |
|-----------------------|--|
| Certifications | CE, FCC, UL/CUL, NOM, RoHS, UKCA |
| Environment | |
| Operating Temperature | 0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing |
| Storage Temperature | -20°C ~ 60°C, 20% ~ 90% RH. Non-Condensing |
| Optional Peripheral | |
| Expansion Hub | MA-HUB-A1 |
| MSR | MA-MSR-A1 |
| Camera | MA-CAM-A1 |
| Light Bar | MA-LBAR-A1 |
| Bar Code Scanner | MA-SCAN-A1 |



The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2023 TES America, LLC. All rights reserved. MT22-1116