

OF-150S-B1(B2)

15" Surface Capacitive Touch Monitor



Description

The OF-150S-B1(2), a robust metal chassis display using industry-standard surface capacitive touch technology, provides a durable, optically enhanced, and cost competitive alternative to 5-wire resistive displays used in industrial automation equipment and kiosk enclosures. The OF-150S-B1(2) display offers multiple mounting options to make integration easy and a variety of bezel options for sealing against liquids and other contaminants. A remote on-screen display module helps simplify any changes to the display image during installation or system maintenance.

Featured Specifications

- Size: 15" TFT LCD
- Maximum Resolution: 1024 x 768
- Contrast Ratio: 500:1
- Aspect Ratio: 4:3
- Brightness: 250 nits (No Touch), 225 nits (S-CAP)
- Video Port: 1 x 15 Pin D-Sub (VGA)
- Warranty: 3 year

Specifications

Touch LCD Display

Touch Screen	Surface Capacitive
Touch Points	Single Touch
Touch Screen Interface	USB (11-71315-225-01 B1) or Serial (11-71315-227-01 B2)

I/O Ports

Serial Port	1 x RJ45
USB Port	1 x USB Type B
Video Port	1 x 15 Pin D-Sub (VGA)
Audio Port	–
Power Input	1 x 12V DC or 110/220V AC

Physical Properties

Speaker	–
Housing Color	Silver
Construction	Glass, Plastic (ABS), SECC Metal
Compliance	IP66/NEMA 4X (industrial bezel)
Dimensions (W x H x D) mm	350.4 x 277.3 x 50
Net Weight (kg)	4.2
Gross Weight (kg)	9.2
Carton (W x H x D) mm	445 x 381 x 165
VESA	75 x 75mm

Safety

Certifications	FCC B, CE, UL/cUL
----------------	-------------------

Environment

Operating Temperature	0°C ~ 40°C, 20% ~ 90% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing

Optional Peripheral

Industrial Bezel	IB-150-A1 (29368)
Contour Bezel	CB-150-A1 (29369)
RJ45 OSD Remote	REM45-A1

