

SK-215P-A1

21.5" PCAP 3-in-1 Touch Monitor



Description

The commercial-grade, SK-215P-A1, is a Full HD wide format convertible monitor perfect for a wide range of applications, embedded or exposed, that requires quality and reliability in high use environments. Versatile by design, this 21.5" wide monitor fits a variety of applications with the ability to withstand harsh conditions while retaining high performance levels. The IP65 rating coupled with an updated I/O selection for seamless integration and OSD controls built into the back housing create a user experience that is effortless and simplistic.

Featured Specifications

- Size: 21.5" TFT LCD
- Maximum Resolution: 1920 x 1080
- Contrast Ratio: 1000:1
- Aspect Ratio: 16:9
- Brightness: 250 nits (No Touch), 217 nits (P-CAP)
- View Angle: H:178°, V:178°
- Video Port: 1 x VGA (DB15), 1 x HDMI, 1x DP
- Warranty: 3 year

Stand sold separately
Part #IS-000-A1

Specifications

Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Type B)

I/O Ports

Serial Port	1 x RJ45 Remote OSD
USB Port	1 x USB 2.0 (Type B) for Touch Interface
Video Port	1 x VGA (DB15), 1 x HDMI, 1x DP
Audio Port	–
Power Input	1 x 2.1 mm 12V DC Jac

Physical Properties

Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	–
Housing Color	Black
Construction	Glass, SECC Metal, Plastic (ABS)
Compliance	Front Panel IP65 Compliant, Rear IPX1
Dimensions (W x H x D) mm	517.4 x 313.3 x 46.0 mm
Net Weight (kg)	4.4 kg
Gross Weight (kg)	6.8 kg
Carton (W x H x D) mm	610 x 405 x 160 mm
VESA	100 x 100 mm
Ball Drop	–

Safety

Certifications	CE/FCC/UL(62368)/TUV (60950)/CCC/BSMI/LVD(65950)
----------------	--

Environment

Operating Temperature	0° C ~ 40° C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20° C ~ 60° C, 10% ~ 90% RH. Non-Condensing

Optional Peripheral

Industrial Stand	IS-000-A1 (Sold Separately)
Remote OSD	Rem45-A1 (Sold Separately)

