## **TX Series**



# **POSIFLEX**

#### **KEY FEATURES**

- Small-form factor industrial PC for retail and hospitality verticals, ideal for digital menu boards & signage, kitchen video, and more
- Flexible use for all verticals, cache box, kitchen video and more
- VESA mounting for flexible deployment
- Industrial-class embedded CPU and operating systems
- Compact size with ultra small footprint
- Fanless and ventless
- Ruggedized design

#### TX2300

- Intel® Celeron® J6412, 1.5MB L2 Cache, 2.0GHz
- 2x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz 1.2V

#### TX5300

- Intel® Core™ i3-8100T, 6M Cache, 3.10GHz; Intel® Core™ i5-8500T, 9M Cache, 3.50GHz
- 2x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz 1.2V

### Multi-Purpose Controller



The small footprint and VESA mounting points of TX Series allow easy installation in anywhere you need a fully functional, small foot print / small form factor PC. With patented fan-free architecture,

TX Series is suitable for a wide range of environments and applications from the hot kitchen area, to the salty air of coastal environments, to anywhere silent operation is required.



TX Series			
Specifications	TX2300	TX5300	
Processor	Intel® Celeron® J6412, 1.5MB L2 Cache, 2.0GHz	Intel® Core™ i3-8100T, 6M Cache, 3.10GHz Intel® Core™ i5-8500T, 9M Cache, 3.50GHz	
System Memory	2 x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz, 1.2V	2x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz 1.2V	
Storage Device	1 x M.2 128GB SSD (supporting AHCl Mode)	2 x SATA; 1 x M.2 (Supporting SATA)	
Supported OS	Windows 10 loT 64bit	Windows 10 IoT 64bit	
Physical Dimensions			
Dimensions (WxDxH in.)	8.6 x 7.9 x 2.2	8.6 x 7.9 x 3.2	
Weight (lbs)	2.5	8	
Connectivity			
LAN Port	1 x Gigabit LAN	2 x Gigabit LAN	
Serial Port	2 x DB9 Serial; 2 x RJ-50 Serial (5v/12v support on all COM ports)	4 x DB9 Serial; COM5/COM6 via optional cable (5v/12v support on all COM ports)	
Video Ports	1 x VGA; 2 x HDMI (12v support on VGA for Posiflex monitors)	1 x VGA; 1 x HDMI (12v support on VGA for Posiflex monitors)	
USB Port	2 x USB 3.0; 4 x USB 2.0	4x USB 3.0	
Line Out Port	Yes		
Parallel Port	Yes, via optional cable		
Mini PCI-Express Expansion Slot	Yes, M.2 slot for WiFi		
CR Port	1 x RJ-11 controls 2 cash drawers		
Powered USB	N/A	1 x 24v, 2 x 12v	

<sup>\*\*</sup> The product information and specifications are subject to change without prior notice.

MONITOR	RECEIPT PRINTER	CASH DRAWER
Touch Monitor - TM8115 5-Wire USB Resistive Touch Screen	Thermal Printer - PP9000 USB + Optional Serial, Parallel, LAN or Wireless	Cash drawer - CR6300 Printer driver and USB options available





www.posiflexusa.com

















