TX2300






KEY FEATURES

- Intel® Celeron® J6412, 1.5MB L2 Cache, 2.0GHz
- 2x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz 1.2V
- Small-form factor industrial PC for retail and hospitality verticals, ideal for digital menu boards & signage, kitchen video, and more
- Flexible use for all verticals, cache box, kitchen video and more
- VESA mounting for flexible deployment
- Industrial-class embedded CPU and operating systems
- Compact size with ultra small footprint
- Fanless and ventless
- Ruggedized design

Multi-Purpose Controller



The small footprint and VESA mounting points of TX Series allow easy installation in anywhere you need a fully functional, small foot print / small form factor PC. With patented fan-free architecture,

TX Series is suitable for a wide range of environments and applications from the hot kitchen area, to the salty air of coastal environments, to anywhere silent operation is required.



Multi-Purpose Controller		
Specifications	TX2300	
Processor	Intel® Celeron® J6412, 1.5MB L2 Cache, 2.0GHz	
System Memory	2x slot 4GB DDR4 SO-DIMM (Max. 32GB), 2666 Mhz, 1.2V	
Storage Device	1 x M.2 128GB SSD (supporting AHCl Mode)	
Supported OS	Windows 10 IoT Enterprise LTSC 64bit	
Physical Dimensions		
Dimensions (WxDxH in.)	8.6 x 7.9 x 2.2	
Weight (lbs)	2.6	
Connectivity		
LAN Port	1 x Gigabit LAN	
Serial Port	2 x DB9 Serial; 2 x RJ-50 Serial (5v/12v support on all COM ports)	
Video Ports	1 x VGA; 2 x HDMI (12v support on VGA for Posiflex monitors)	
USB Port	2 x USB 3.0; 4 x USB 2.0	
Line Out Port	Yes	
Parallel Port	Yes, via optional cable	
Expansion Slot	Yes, M.2 slot for WiFi	
CR Port	1, control 2 x cash drawer, support 24V CR	
Powered USB	N/A	

^{**} The product information and specifications are subject to change without prior notice.

MONITOR	RECEIPT PRINTER	CASH DRAWER
Touch Monitor - TM8115 5-Wire USB Resistive Touch Screen	Thermal Printer - PP9000 USB + Optional Serial, Parallel, LAN or Wireless	Cash drawer - CR6300 Printer driver and USB options available





www.posiflexusa.com

SAP® ORACLE® (intel)

FC CE Q