

sewoo

3-Inch POS Printer

SLK-TS200



- Simple and sleek design
- High Performance Easy Maintenance
- Wheel-type paper jam control
- High speed printing at 250mm/sec(9.8ips)
- Visible wireless connectivity status
- Ideal for top exit printing with wall mount
- Simple and easy replacement of components including head, motor, cutter, PCB, etc



WiFi




Bluetooth



Barcode



Durable



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 250mm/sec(9.8ips)

Print Width

Up to 72mm(2.8")

Resolution

203dpi

Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

Sensor

Paper end, Cover open

Reliability

TPH life : 150km

MCBF : 80 Million lines

Cutter life : 2.0 Million cuts

Cutter method: Partial / Full cut
(Command or tool setting)

Speaker

3type built in melody

Drawer port

1 circuit(24V, Max. 1A)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

174×136×132mm

(6.85"×5.35"×5.19")

Weight

1.04Kg(2.3lb)



INTERFACES

Standard

USB(B type)+Serial

(RS- 232C_9pin)+Ethernet Built-in

Optional

Bluetooth Smart Ready

(Bluetooth5.0+BLE)

or WiFi(802.11a/b/g/n)



CERTIFICATIONS

KC, CE, FCC, IC, CB,
cTUVus, Energy Star



OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 113°F(0 ~ 45°C)

Operating Humidity

10 ~ 80%

Storage Temperature

4 ~ 140°F(-10 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Black mark paper

Media Width

Max.58mm/80mm(3.14")

Media Core Diameter

12.5mm ± 0.5mm(0.4")

Media Roll Diameter

Max. ø 83mm(3.2")

Thickness

0.06~0.08mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),
Linux Driver, Mac Driver, OPOS Driver,
JavaPOS Driver

SDK

Android SDK, iOS SDK, Windows SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar

2D

PDF 417, QR code



FONTS/GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

· 180dpi

Font A(12x24) : 42/30cpl

Font B(9x17) : 59/40cpl

· 203dpi

Font A(12x24) : 48/35cpl

Font B(9x17) : 64/46cpl

Character set

95 Alphanumeric,

16 International,

128 x 18 Graphic



ACCESSORIES

Optional

Melody box, 24V Buzzer,

2inch Paper Guide

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

