## Key Features


10-Point Multi-Touch | SuperClear® IPS Panel
Technology | Ergonomic Dual-Hinge Design | Optimized
Stylus Pen | Loaded With Connectivity



## Product **Description**

With responsive, in-cell touch technology and an advanced ergonomic design, the ViewSonic TD2455 touch display delivers hands-on control for more productive workspaces and collaborative classrooms. This 24" (23.8" viewable) Full HD display features a SuperClear IPS panel and a three-sided ultra-thin bezel design that lets you see more and do more with incredible images and expansive screen real estate. An intuitive 10-point Projected Capacitive (PCAP) touch screen delivers a smooth and responsive experience with every tap, pinch, and swipe. Its advanced ergonomic design delivers versatility and comfort for office use, check-in applications, and more. With DisplayPort out connectivity, the TD2455 easily connects to a projector or interactive whiteboard, making it ideal for use as a podium touch display option in classrooms and lecture halls. An included stylus pen lets you write or draw on screen, and easily attaches to the magnetic base of the display stand for secure storage and quick access. The stand also features an integrated client mount\* for quick installation of VDI client endpoints on the back of the screen. So whether used on its own on office desktops, as a collaboration station in corporate huddle spaces, or as a front-of-classroom interactive teaching hub, the TD2455 helps to boost efficiency and productivity. \*Client Mount Kit sold separately











- all: 888.881.8781
- email: salesinfo@viewsonic.com

07

0 08 0 09

0 10 0 11

visit: viewsonic.com

Display:	
Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS
Resolution:	1920 x 1080
Resolution Type:	HD (1920x1080)
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Color Space Support:	6 bit + Hi-FRC
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	6ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate (Hz):	60
Compatibility:	
PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
Connector:	
HDMI 1.4 In(1), Display Port(1), Disp	en 1 Type B(1), USB 3.2 Gen 1 Type C(1), play Port Out(1)
Touch:	
Touch Technology:	Projective Capacitive
Touch Points:	10-Point Touch
Touch Compatibility:	Supports Windows 7/8/10, Linux Kernel Ubuntu 18.04/19.04, and Chromebox
Audio:	
Internal Speakers:	2W (x2)
Power:	
Eco Mode (Conserve):	11.3
Eco Mode (optimized):	14.5
Consumption (typical):	19.6
Consumption (max):	23.6
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.3W
Power Supply:	Internal
Additional Hardware:	
Kensington Lock Slot:	1

Controls:	
Physical Controls:	1,2,3,4,5,6 [Power]
On Screen Display:	Auto image adjust, Contrast/Brightness, Input Select, Audio adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Operating Conditions:	
Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%
Mount:	
VESA Compatible:	100 x 100 mm
Video Signal:	
Frequency Horizontal:	15 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz
Video Input:	
Digital Sync:	TMDS for HDMI (v1.4), Micro-Packet for DisplayPort (v1.2), and USB Type C
Ergonomics:	
Tilt (Forward/Back):	5° / 60°
Weight (imperial):	
Net (lbs):	14.2
Net Without Stand (Ibs):	8.2
Gross (lbs):	18.6
Weight (metric):	
Net (kg):	6.4
Net Without Stand (kg):	3.7
Gross (kg):	8.4
Dimensions (imperial) (WxHxI	
Packaging (in.):	24.3 x 16.3 x 11.2
Physical (in.):	21.2 x 16.8 x 11.3
Physical Without Stand (in.):	21.2 x 12.6 x 2.0
Dimensions (metric) (WxHxD)	:
Packaging (mm):	617.0 x 415.0 x 285.0
Physical (mm):	539.0 x 426.0 x 286.0
Physical Without Stand (mm):	539.0 x 320.0 x 52.0
General:	
Energy	03, Energy Star, EPEAT, CEC, MX-CoC, Mexico
Passive Touch Pen, Passive Touch	
laws.	of in accordance with local, state or federal
Warranty: Three-year limited warra	anty on parts, labor and backlight
UPC: 766907004960	
Accessories:	
CB-00009950, CB-00010684, CB-0 DMA-002, LCD-WMK-001, PG707V	00010958, CB-00012984, LCD-DMA-001, LCD- N, PG707X