

# TC52 and TC57 Series Touch Computer

## The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



### The ultimate user experience

### Android for instant familiarity

Your workers already know how to use an Android device, virtually eliminating training time and adoption curves. And you can deliver the highly-graphic interactive apps today's workers expect.

### Advanced touchscreen technology

Give your workers touchscreen simplicity. The 5 in. display offers plenty of real estate for graphics-intensive intuitive applications. The easy, familiar and flexible multi-touch operation works even when wet, with a gloved finger or a stylus. And with best-in-class outdoor readability, the screen is easy to read, even in bright sunlight.

### Easily capture it all — barcodes, labels and documents

Advanced scanning technology and PRZM Intelligent Imaging deliver lightning fast capture of printed and electronic 1D and 2D barcodes, including Digimarc — regardless of condition. The expanded working range and wide field of view allow workers to scan barcodes nearer and farther away, while omnidirectional scanning delivers true point and shoot performance — no need to ever align the device with the barcode.

Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

### Full shift power your workers can count on

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>2</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

### Active Edge™ Touch Zone for One-touch Feature Access

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

### All the latest technology advancements

### Rugged and ready for the toughest business day

While these touch computers look like smartphones, the similarities stop there — they are engineered for the enterprise, inside and out. You can drop it in water or on concrete and use it in dusty areas, out in the rain or snow — and still expect reliable operation. The unibody design provides extra impact protection for the sensitive electronics. And the Corning Gorilla Glass touch panel and imager window bring maximum scratch-resistance and shatter-proofing to two of the most vulnerable device features.



### A platform to handle all your apps — today and tomorrow

The ultra-powerful processor provides superior performance on all voice and data apps. You also get built-in support for the next two versions of Android (P and Q)<sup>1</sup> and future apps, such as artificial intelligence.

### Rich locationing support

Easily implement locationing with support for many technologies, including Visible Light Communication (VLC), Bluetooth 5.0 BLE and WiFi, plus Zebra's SmartLens<sup>3</sup> and MotionWorks solutions.

### Support for the latest WiFi enhancement improves WiFi range and speed - with less power

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

### The highest quality voice in its class

Three microphones, high-volume speakers and noise-cancellation technology work together to ensure that callers on both ends of every call can hear every word — even in the noisiest areas.

### New 5 MP front-facing camera supports more advanced apps

With the new front-facing camera, you get built-in support for the latest positioning technology, Visible Light Communication (VLC) which allows you to track the location of shoppers and workers with compatible overhead LED lighting. Video calling improves service and productivity. Customers enjoy a more personal touch — and remote experts can see a repair in process to help onsite technicians resolve issues faster and increase first-time-fix rates.

### Complete cellular network flexibility with single device simplicity

The TC57 provides all workers anywhere in the world with dependable cellular service. Support for carrier aggregation substantially improves application performance by increasing data capacity and speeds. And support for the powerful Public Safety LTE network provides the reliable communications first responders need, eliminating network congestion concerns and providing the interagency operation required for improved situational awareness.

### Ultra high-resolution photos and videos

The 13 MP color rear camera captures highly detailed photos and videos - ideal for proof-of-condition/delivery/service, onsite technical support and more.

### Bluetooth 5.0 for twice the speed and four times the range - with less power

Improved data speeds up to 2 Mbps increases application flexibility and performance for Bluetooth peripherals, such as printers and headsets, while Bluetooth Low Energy reduces power requirements to extend battery cycle times.

### Maximize productivity with enterprise accessories

Unlike consumer smartphones, you get a full suite of backward compatible business-class accessories that make the TC52/TC57 easier to use and manage, from a snap-on trigger handle for easier scanning to unique ShareCradles that charge it all — devices and batteries.

### Drive workforce productivity, efficiency and device value to a new level with powerful new Mobility DNA apps

### WorryFree WiFi — dependably superior WiFi, delivered

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

### PowerPrecision Console — prevent aging batteries from reducing workforce productivity

This free PC-based solution provides an easy-to-read dashboard that allows you to quickly identify and remove aging batteries from your battery pool — before they impact workforce productivity and mobile device uptime.

### End-to-end revolutionary control of the update process with LifeGuard

Updating your enterprise-class Android mobile devices is often time-consuming, costly, complex and difficult to track. Now you can do it all with LifeGuard Analytics — free with your Zebra OneCare Support contract. View available updates along with priority and which devices are eligible for the update. Automatically update your devices over the air with the press of a button. And easily monitor and manage the status of updates in real time.

### Easily manage access to Google Mobile Services (GMS) with **Restricted Mode**

StageNow's new Restricted Mode delivers an industry first — an easy way to simply click to deactivate Google Mobile Services (GMS) that come standard with the operating system — and reactivate should you need them down the road. StageNow is free and pre-loaded on every TC52/TC57

### The ultimate in device management options

### Improve device value with Zebra's optional Visibility Services

Get the device management data you need to take device uptime, operational efficiency and the return on investment to the next level. Asset Visibility Service (AVS) is an easy to use and deploy solution that doesn't require an Enterprise Mobility Management (EMM) system. Operational Visibility Services (OVS) is a comprehensive device management solution that leverages your EMM information to help get more value out of your Zebra mobile devices. These optional services can be added to your optional Zebra OneCare support contract.3

# **TC52/TC57 Series Specifications**

Dimensions         6.1 in. L x 2.9 in. W x 0.73 in. H 155 mm W x 18.6 mm H           Weight         8.8 oz./249 g with battery           Display         5.0 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel           Imager Window         Corning Gorilla Glass           Touchpanel         Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant antismudge coating           Backlight         LED backlight           Power         Rechargeable Li-lon, PowerPrecision + 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)           Expansion Slot         User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC           SiM Slots         TC57 only: 1 nano SIM           Network         TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client)           Connections         Tigh Speed (Host and Client)           Keypad         On-screen keypad and enterprise keyboard           Voice and Audio         Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth with release ts support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio           Buttons         Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedi	PHYSICAL CHARACTERI	
Display   S.0 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel	Dimensions	
Imager Window Corning Gorilla Glass Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant antismudge coating Backlight LED backlight Power Rechargeable Li-Ion, PowerPrecision +, 4300mAh/15, 48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)  Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC SIM Slots TC57 only: 1 nano SIM Network Connections TC57/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad and enterprise keyboard Voice and Audio Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS CPU Qualcomm Snapdragon* 660 octa-core, 2.2 GHz Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash USER ENVIRONMENT Operating Temp. 4°F to 122°F/-20°C to 50°C Storage Temp. 40°F to 158°F/-40°C to 50°C Tumble Specifications Multiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G Tumble Specifications Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Weight	8.8 oz./249 g with battery
Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant antismudge coating  Backlight  LED backlight  Power  Rechargeable Li-Ion, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)  Expansion Slot  User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC  SIM Slots  TC57 only: 1 nano SIM  Network TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification  Audible tone; multi-color LEDs; vibration  Keypad  On-screen keypad and enterprise keyboard  Voice and Audio Three microphones with noise cancellatior; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons  Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp4°F to 158°F/-40°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boat accessory per MIL STD 810 G  Tumble Specification  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Display	bright, outdoor viewable; optically bonded to
or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant antismudge coating  Backlight  LED backlight  Power  Rechargeable Li-Ion, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)  Expansion Slot  User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC  SIM Slots  TC57 only: 1 nano SIM  Network  Connections  TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification  Audible tone; multi-color LEDs; vibration  Keypad  On-screen keypad and enterprise keyboard  Voice and Audio  Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; High quality speaker phone; PTT headset support; Lellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons  Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU  Qualcomm Snapdragon* 660 octa-core, 2.2 GHz  Operating System  Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory  4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp.  -4°F to 158°F/-40°C to 50°C  Storage Temp.  -40°F to 158°F/-40°C to 50°C	Imager Window	Corning Gorilla Glass
Rechargeable Li-Ion, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)  Expansion Slot  User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC  SIM Slots  TC57 only: 1 nano SIM  Network TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification  Audible tone; multi-color LEDs; vibration  Keypad  On-screen keypad and enterprise keyboard  Voice and Audio  Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; ellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons  Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU Qualcomm Snapdragon* 660 octa-core, 2.2 GHz  Operating System  Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory  4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp.  -4°F to 122°F/-20°C to 50°C  Humidity  5% to 95% non-condensing  Drop Specifications  Multiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14*F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  Vibration  4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Touchpanel	or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti-
4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)  Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC  SIM Slots TC57 only: 1 nano SIM  Network TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification Audible tone; multi-color LEDs; vibration  Keypad On-screen keypad and enterprise keyboard  Voice and Audio Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU Qualcomm Snapdragon* 660 octa-core, 2.2 GHz  Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Backlight	LED backlight
and up to 256 GB SDXC  SIM Slots  TC57 only: 1 nano SIM  Network Connections  TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification  Audible tone; multi-color LEDs; vibration  Keypad  On-screen keypad and enterprise keyboard  Voice and Audio  Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons  Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU  Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz  Operating System  Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory  4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp.  -4°F to 122°F/-20°C to 50°C  Storage Temp.  -40°F to 158°F/-40°C to 70°C  Humidity  5% to 95% non-condensing  Drop Specifications  Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  Sealing  IP67 and IP65 per applicable IEC sealing specifications  Vibration  4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Power	4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery
Network Connections TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN  Notification Audible tone; multi-color LEDs; vibration  Keypad On-screen keypad and enterprise keyboard  Voice and Audio Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash USER ENVIRONMENT Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  Sealing IP67 and IP65 per applicable IEC sealing specifications Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Expansion Slot	•
Connections       High Speed (Host and Client) TC57 Only: WWAN         Notification       Audible tone; multi-color LEDs; vibration         Keypad       On-screen keypad and enterprise keyboard         Voice and Audio       Three microphones with noise cancellation; vibrate alert; Front facing speaker, Bluetooth wireless headset support; High quality speaker phone; PTT headset support; High quality switch voice; HD Voice; and SWB & FB audio         Buttons       Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons         PERFORMANCE CHARACTERISTICS         CPU       Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz         Operating System       Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services         Memory       4GB RAM/32GB Flash         USER ENVIRONMENT       Operating Temp.       -4°F to 122°F/-20°C to 50°C         Storage Temp.       -4°F to 158°F/-40°C to 70°C         Humidity       5% to 95% non-condensing         Drop Specifications       Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G         Tumble Specification       500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specifications         Vib	SIM Slots	TC57 only: 1 nano SIM
Keypad       On-screen keypad and enterprise keyboard         Voice and Audio       Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio         Buttons       Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons         PERFORMANCE CHARACTERISTICS       CPU       Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz         Operating System       Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services         Memory       4GB RAM/32GB Flash         USER ENVIRONMENT       Operating Temp.       -4°F to 122°F/-20°C to 50°C         Storage Temp.       -40°F to 158°F/-40°C to 70°C         Humidity       5% to 95% non-condensing         Drop Specifications       Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G         Tumble Specification       500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification         Vibration       4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random		High Speed (Host and Client)
Voice and Audio       Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio         Buttons       Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons         PERFORMANCE CHARACTERISTICS       CPU       Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz         Operating System       Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services         Memory       4GB RAM/32GB Flash         USER ENVIRONMENT       Operating Temp.       -4°F to 122°F/-20°C to 50°C         Storage Temp.       -40°F to 158°F/-40°C to 70°C         Humidity       5% to 95% non-condensing         Drop Specifications       Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G         Tumble Specification       500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification         Vibration       4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Notification	Audible tone; multi-color LEDs; vibration
vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice; and SWB & FB audio  Buttons  Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU  Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz  Operating System  Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory  4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp.  -4°F to 122°F/-20°C to 50°C  Storage Temp.  -40°F to 158°F/-40°C to 70°C  Humidity  5% to 95% non-condensing  Drop Specifications  Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F)  Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing  IP67 and IP65 per applicable IEC sealing specifications  Vibration  4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Keypad	On-screen keypad and enterprise keyboard
Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons  PERFORMANCE CHARACTERISTICS  CPU Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz  Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Voice and Audio	vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch
CPU Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz  Operating System Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory 4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Buttons	Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume
Operating System  Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services  Memory  4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp.  -4°F to 122°F/-20°C to 50°C  Storage Temp.  -40°F to 158°F/-40°C to 70°C  Humidity  5% to 95% non-condensing  Drop Specifications  Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F)  Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing  IP67 and IP65 per applicable IEC sealing specifications  Vibration  4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	PERFORMANCE CHARA	CTERISTICS
control over GMS and other services  Memory 4GB RAM/32GB Flash  USER ENVIRONMENT  Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz
USER ENVIRONMENT  Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Operating System	
Operating Temp4°F to 122°F/-20°C to 50°C  Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Memory	4GB RAM/32GB Flash
Storage Temp40°F to 158°F/-40°C to 70°C  Humidity 5% to 95% non-condensing  Drop Specifications Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	USER ENVIRONMENT	
Humidity         5% to 95% non-condensing           Drop Specifications         Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G           Tumble Specification         500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification           Sealing         IP67 and IP65 per applicable IEC sealing specifications           Vibration         4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Operating Temp.	-4°F to 122°F/-20°C to 50°C
Drop Specifications  Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification  500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing  IP67 and IP65 per applicable IEC sealing specifications  Vibration  4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Storage Temp.	-40°F to 158°F/-40°C to 70°C
-10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G  Tumble Specification 500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Humidity	5% to 95% non-condensing
tumble specification  Sealing IP67 and IP65 per applicable IEC sealing specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Drop Specifications	-10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the
specifications  Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Tumble Specification	
	Sealing	
	Vibration	

•	CONTINUED)
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition
Electrostatic Discharge (ESD)	+/- 15kv air discharge; +/- 8kv direct discharge; +/- 8kv indirect discharge
INTERACTIVE SENSOR	TECHNOLOGY (IST)
Light Sensor	Automatically adjusts display backlight brightness
Magnetometer	eCompass automatically detects direction and orientation
Motion Sensor	3-axis Accelerometer with MEMS Gyro
Pressure Sensor	Automatically detects altitude information for locating (TC57 only)
Proximity Sensor	Automatically detects when the user places the handset against head during a phone call to disabl display output and touch input
DATA CAPTURE	
Scanning	SE4710 imager (1D and 2D) with extraordinary range Scan range — Code 39 barcode: 20 Mil: 1.8 in. to 32.0 in./4.5 cm to 81.3 cm 3 Mil: 3.1 in. to 5.6 in./7.9 cm to 14.2 cm Digimarc support
Camera	Front — 5 MP; f/2.0 aperture Rear — 13 MP autofocus; f/2.2 aperture; flash LED generates balanced white light; supports Torch mod
NFC	ISO 14443 Type A and B; FeliCa and ISO 15693 cards; P2P mode and Card Emulation via Host. TC57 Only: Card Emulation via Host and UICC
WIRELESS WAN DATA	AND VOICE COMMUNICATIONS (TC57 ONLY)
Radio Frequency Band	Supports VoLTE, Carrier Aggregation up to 3DL CALTE FDD: 700/800/850/900/1800/1900/ AWS/2100/2600 (28,13,14,12,17/19,20/5,26/8/3/2,25/4,66/1/7); LTE TDD: 1900/2300/2500 (39/40/41,38); UMTS/HSPA/HSPA+: 850/900/AWS/1900/2100 (5/8/4/2/1); GSM/GPRS/EDGE: 850/900/1800/1900
GPS	TC57 only: Autonomous, Concurrent GPS; GLONASS; Gallileo; BeiDou, and A-GPS. Supports IZAT™ XTRA
Multimedia	Wi-Fi Multimedia™ (WMM) and WMM-PS; Including TSPEC
WIRELESS LAN	
Radio	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v³/w; Wi-Fi™ certified; IPv4, IPv6, 2x2 MU-MIMO TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v³/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps
Operating Channels	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11,12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52 56,60,64,100,104,108,112,116,120,124,128,132,136,14 0,144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency.

### TC52/TC57 Series vertical markets and applications:

### **RETAIL ASSOCIATES**

- Price/inventory Checks
- Loyalty apps
- Item locator
- Price management
- Line busting/POS
- · Assisted selling
- Electronic coupons
- Store transfers
- · Gift registry lookup

### **RETAIL MANAGERS**

- Workforce management
- Planogram management
- Promotion compliance
- Merchandising

### DIRECT STORE **DELIVERY DRIVERS**

- Order automatiion
- · Delivery tracking
- Inventory management
- Customer support

### FIELD SERVICE **TECHNICIANS**

- Asset management
- · Parts inventory
- Invoicing
- · Scheduling and location-based services

### LIGHT COURIER **DRIVERS**

- Proof of delivery
- Asset management
- Location services
- Invoicing

# **TC52/TC57 Specifications (continued)**

# WIRELESS LAN (CONTINUED) Security and WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPV2), EAP-TLS, PEAPV0-MSCHAPV2, PEAPV1-EAP-GTC and LEAP.EAP-PWD Certifications WFA (802.11n, WMM-PS, 801.11ac, PMF) Fast Roam PMKID caching; Cisco CCKM; 802.11r; OKC WIRELESS PAN Bluetooth Class 2, Bluetooth v5.0, Bluetooth Low Energy (BLE)

Subject to the terms of Zebra's hardware warranty statement, the TC52/57 Series is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit:

www.zebra.com/warranty

WARRANTY

### RECOMMENDED SERVICES

Zebra OneCare Essential and Select support services
Zebra Visibility Services — Asset Visibility Service (AVS) and
Operational Visibility Service (OVS)<sup>3</sup>

- Upgrading to new supported versions of Android requires the purchase of a Zebra OneCare Service contract
- 2. Based on typical user profiles
- 3. Available Q1 2019

Specifications subject to change without notice.



### MOBILITY DNA SOFTWARE

Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna



















